

## TABLE POSITIONER - U001395T TR700-V1 - Capacity: 700 kg



|                        |                     |   |                                    |
|------------------------|---------------------|---|------------------------------------|
| <b>Make &amp; Type</b> |                     | TR700-V1  |                                    |
| <b>Capacity</b>        |                     | 700 kg  | 170 mm C.O.G. from table surface   |
| <b>Tilting Moment</b>  |                     | 200 kgm   | (calculated from tilting trunions) |
| <b>Rotating Torque</b> |                     | 130 kgm   |                                    |
| <b>Table</b>           | <b>Size</b>         | Ø 900 mm  |                                    |
|                        | <b>Type</b>         | Fitted with 4 radial T-slots for workpiece fastening              |                                    |
|                        | <b>Support type</b> | Central axis and twin bearings                                    |                                    |
| <b>Table eight</b>     |                     | Of table plate placed horizontal                                  | 900 mm                             |
|                        |                     | Of rotation axis with table placed vertical                       | 785 mm                             |
| <b>Table tilting</b>   |                     | Electromechanical, trough speed reducer and geared sector: 0÷135° |                                    |
| <b>Table rotation</b>  |                     | Electromechanical   |                                    |



|                                       |                      |   |  |
|---------------------------------------|----------------------|---|--|
| <b>Rotation speed</b>                 |                      | 0,09÷2,5 rpm  | Controlled by inverter and potentiometer on hand control |
| <b>Controls &amp; electric system</b> | <b>Control panel</b> | On/Off switch – Automatic/Manual rotation –<br>Rotation speed control on handcontrol/controlpanel-<br>Emergency stop<br>Input: 380V |  |
|                                       | <b>Hand control</b>  | Table tilting up/down - Emergency stop  |  |
|                                       | <b>Foot control</b>  | Rotation forward/stop/reverse – Emergency stop  |  |
| <b>Dimensions</b>                     | <b>Base</b>          | 1.100 x 880 mm  |  |
|                                       | <b>Overall</b>       | 1.250 x 1.000 x (H) 900 mm  |  |
| <b>Machine weight</b>                 |                      | 500 kg  |  |
| <b>Fabrication year</b>               |                      | 2016  |  |
| <b>Machine history and repair</b>     |                      |   |  |
| <b>Notes</b>                          |                      | Matr. 232/16  |  |



