



A.NARDUCCI

WELDING PRODUCTS

TABLE POSITIONER

A.Narducci Testudo P10E - capacity: 10.000 kg



Make & type		A.Narducci Testudo P10E	
Capacity	10.000 kg	@ 800 mm from table surface	
Tilting moment	8.000 kgm	Calculated from table plate	
Rotating torque	1.500 kgm		
Table	Size	Ø 1.900 mm	
	Type	Welded frame plate with radial T-slot for workpiece fastening	
	Support type	Slewing ring bearing	
Table height	Of table plate, placed horizontal	1.100÷2.600 mm (to be confirmed)	
	Of rotation axis, with table placed vertical	1.500÷3.000 mm (to be confirmed)	
Table tilting	Hydraulic, trough double cylinders		
Table rotation	Electromechanical, trough motorgear		
Table height adjustment	Hydraulic, trough double cylinders		

POSITIONER - A.Narducci P10E - 10.000 kg

Rotation speed		0,065 ÷ 1,00 rpm. Adjusted with potentiometer
Controls & electric system	Control panel	Placed onboard Fitted with connecting plugs for handcontrol, footcontro, motor, valve, endswitches cables Input: 380V - ThreePhase
	Hand control	<ul style="list-style-type: none"> ▪ Buttons for Power and Rotation forward/stop/reverse ▪ Table tilting up/down ▪ Table elevation up/down ▪ Potentiometer for rotation speed reggulation ▪ Emergency stop
	Foot control	<ul style="list-style-type: none"> ▪ On request ▪ FORWARD/STOP/REVERSE SWITCH
Dimensions	Base dimension	2.850 x 1.900 mm (to be confirmed)
	Overall dimensions	3.300 x 1.930 x (h) 1.100 mm (to be confirmed)
Machine weight		~9.000 kg
Notes		



